

# MORE PRECISION IN EVERY PIXEL



IQ Quattro captures every detail because of its advanced 48-bit CIS technology passing the best 24-bits to the file at up to 1200 dpi optical resolution.

Faster: Spend less time scanning and instead focus on what matters to you.

**Better:** Shadows and unwanted background are suppressed leaving you with crisp, sharp and natural scans – ready to be used in your continued workflow.

**Unique technology**: With Contex CleanScan CIS modules, superfast Ethernet and award-winning Nextimage software, Contex IQ Quattro 24 is the perfect scanner for technical projects with smaller original sizes.

### Powered by X-Rite®

The ICC Color Management in Nextimage 6 software is made with X-Rite® color profiling.

## **High productivity**

Designed for the most demanding high-production environments.

#### Green

Energy Star® compliant using only 0.5 W in standby mode.

# Compatible

Compatible with AutoCAD®, ESRI® and many other software applications.

#### Adiustable

Adaptable floor stands for standalone and MFP configurations.

### **Printer drivers**

Copy and print to HP, Canon, Epson and Océ printers. See the full list at contex.com/nextimage-supported -printers.






|  | IQ QUATTRO 2490  |
|--|--|
| Scanning Speed¹ (inch/sec.) while scanning 24-inch wide document |  |
| 200 dpi (color, grayscale, monochrome)                           | 14   |
| Maximum scan width   | 24 inches (610 mm)   |
| Maximum media width  | 26.6 inches (676 mm)   |
| Working height <sup>2</sup>                                      | 32.8/33.8/34.8 inches (834/859/884 mm)   |
| Optical resolution   | 1200 dpi   |
| Maximum resolution   | 9600 dpi   |
| Total number of pixels   | 32400 pixels   |
| CIS technology <sup>3</sup>                                      | Contex CleanScan   |
| Contex SIGMA <sup>4</sup>  | Included   |
| Contex CFR <sup>5</sup>  | Included   |
| Maximum media thickness  | 0.08 inch (2 mm) flexible documents only   |
| Accuracy   | 0.1% +/-1 pixel  |
| Data capture (color/mono)  | 48-bit / 16-bit  |
| Color space  | Adobe RGB, Device RGB, sRGB  |
| USB with xDTR  | Included   |
| Gigabit Ethernet with xDTR2                                      | Included   |
| Cloud enabled  | Yes  |
| Energy Star® certified   | Included   |
| Included software <sup>6</sup>                                   | Nextimage 30 day trial (incl. TWAIN driver, excl. licence)   |
| Optional software  | Nextimage Scan & Archive, Nextimage Repro  |
| File formats <sup>7</sup>  | TIF, JPG, PDF, PDF/A, DWF, CALS, BMP, JPEG-2000(JP2), JPEG2000 Extended(JPX), TIF-G3, TIF-G4, others |
| Operating systems  | Windows 11 64-bit, Windows 10 64-bit, Windows Server 2022 Standard Edition                           |
| Power consumption  | Ready: 10W. Sleep mode: 0.5W. Scanning: 18W  |
| Power requirements   | 100-240V, 60/50Hz, 18W   |
| Weight   | 35.5 lbs. (16.1 kg)  |
| Dimensions (L×W×H)   | 32.4×18.9×6.3 in (823×480×160 mm)  |
| Certifications/compliance  | CE, cUL, Customs Union, Ukr, VCCI, FCC Class A, RoHS and ENERGY STAR® certified                      |
| Country of origin  | Designed and engineered in Denmark. Manufactured in China.   |


- 1. Scanning speeds depend on document width and computer configuration. Contex recommends Intel Core i5, AMD Ryzen 5 5500, or better 64-bit processors, 16 GB RAM and SSD SATA drive, min. USB 3.0 or Gigabit Ethernet. 2. Requires optional scanner stand.
- 3. Contex CleanScan technology is based on custom CIS modules with dual-sided LED light and Dual Diffusion.
- 4. Signal Intensity Matching (SIĞMA) is a Contex patent. Sensor heating during a scan can cause inhomogeneous images. Thanks to Contex innovative thinking Contex IQ Quattro scanners will minimize sensor differences LIVE during a scan.
- 5. Color Fringe Removal (CFR) is an advanced Contex patented filtering technology designed to remove the fringes inherent in CIS strobing scanning devices.
- 6. Contex applications creates industry standard raster file formats that can be used in any CAD or GIS application.
- 7. Requires optional Nextimage software

All trademarks remain the property of their respective holders, and are used only to directly describe the product being provided. Their use does not indicate a relationship between Contex and the trademark holders.

# IQ Quattro gives you fast results combined with excellent image quality



Contex CleanScan CIS The IQ Quattro Scanners are equipped with Contex CleanScan CIS modules which facilitate optical image quality with dual-sided LED lighting. This eliminates creases and folds in originals normally a challenge for CIS scanners, and thus provides clear, crisp scans every time.



# Color fringe removal (CFR) technology Color Fringe Removal (CFR) is an

advanced Contex patented filtering technology designed to remove the fringes inherent in CIS strobing









Contex solutions are compatible with all leading large-format printers.







